

Comprehensive Finished Street Name Signs Checklist

Easy Order Checklist:

1 Select Blade

- ☐ Flat Blade .080" Aluminum
- ☐ Extruded Blade NO RADIUS
6" and 9" Blade Heights Only
- ☐ Econo Vandal Resistant
3MM ACM MATERIAL - NO SCRAP VALUE
6", 8" and 9" Blade Heights Only

2 Reflective Type

- ☐ High Intensity Prismatic
- ☐ DG3 MUTCD guidance - Foreground and overhead mounted signage: White reflective must be > 120 candlepower, Green must be > 7.

3 Color Scheme

- ☐ White on Green
- ☐ White on Blue
- ☐ White on Brown
- ☐ Black on White
- ☐ White on Black
- ☐ Other/Custom

MUTCD guidance - Acceptable alternative background colors to Green are Blue, Brown or White. The legend shall be White, except for Black on White signs. Custom colors require adequate contrast, call a customer service specialist for guidance.

4 Sides

- ☐ Double Face Ground Mount
- ☐ Single Face Overhead Mount

5 Border

MUTCD guidance - Borders are optional, but if used, must be the same color as the letters.

- ☐ None
- ☐ Edge -Should use on dark backgrounds
- ☐ Inset -Should use on white backgrounds

6 a. Logo or Route Symbol

- ☐ None MUTCD guidance - Route symbols or Logos may be placed on the left side of a sign.
- ☐ Yes The maximum height is the same as the letter height.

6 b. Prefix/Suffix

- ☐ Full Size
- ☐ Half Size

MUTCD Guidance - Prefix/Suffix Height may be smaller than the height of the primary copy and may be abbreviated. No punctuation is to be used.

7 Vandal Resistant

Hole Punch

- ☐ None
- ☐ VPA 12 Bolt thru
- ☐ Other

Roadway Type Local Two Lane Roads 0-25 MPH

MUTCD guidance - Initial upper-case letters at least 4" high and lower-case letters 3/4 height of upper-case.

8 Dimensions



Maple St

Blade Height: 6" | Corner Radius .75"
Letter Height/Prefix: 4" | Suffix Height: 2"
Font: Highway Gothic B | Case: U/L

Hickory Ln

Blade Height: 8" | Corner Radius .75"
Letter Height/Prefix: 4" | Suffix Height: 2"
Font: Highway Gothic B | Case: U/L

Two Lane Roads Over 25 MPH and Multi Lane Roads 0-40 MPH

MUTCD guidance - Initial upper-case letters at least 6" high and lower-case letters 3/4 height of upper-case.



Second St

Blade Height: 9" | Corner Radius .75"
Letter Height/Prefix: 6" | Suffix Height: 3"
Font: Highway Gothic B | Case: U/L

Seventh St

Blade Height: 12" | Corner Radius 1.5"
Letter Height/Prefix: 6" | Suffix Height: 3"
Font: Highway Gothic B | Case: U/L

Multi Lane Roads Over 40 MPH

MUTCD guidance - Initial upper-case letters at least 8" high and lower-case letters 3/4 height of upper-case.

Cherry Rd

Blade Height: 12" | Corner Radius 1.5"
Letter Height/Prefix: 8" | Suffix Height: 4"
Font: Highway Gothic B | Case: U/L

Overhead Mast Arm

MUTCD guidance - Initial upper-case letters at least 12" high and lower-case letters 3/4 height of upper-case.

Hillside Dr

Blade Height: 18" | Corner Radius 1.5"
Letter Height/Prefix: 8" | Suffix Height: 8"
Font: Highway Gothic C | Case: U/L

E Tombigbee St

Blade Height: 18" | Corner Radius 1.5"
Letter Height/Prefix: 8" | Suffix Height: 4"
Font: Highway Gothic C | Case: U/L

Holly Ct

Blade Height: 24" | Corner Radius 1.5"
Letter Height/Prefix/Suffix Height: 12"
Font: Highway Gothic C | Case: U/L

51 Terry Rd

Blade Height: 24" | Corner Radius 1.5"
Letter Height/Prefix: 12" | Suffix Height: 6"
Logo/Route Symbol Height: 12"
Font: Highway Gothic C | Case: U/L

Street Name Signs are Priced based on Length. Please e-mail or fax your list of signs, along with the specifications you've selected for a personalized quote.

Street Name Signs MUST be Type II copy on Type I background or better.
We recommend using **3M High Intensity Prismatic** for **Ground Mounted SNS**
and **3M Diamond Grade Cubed** for **Overhead Mounted SNS**

IMPORTANT NOTE: Please e-mail or fax your list of signs (MUST BE A TYPED LIST), along with the specifications you've selected above for a personalized quote. Prefixes/Suffixes MUST use MUTCD Abbreviation, No Punctuation, Special Characters or Block Numbers allowed. Street Name Signs are Priced based on Length.